

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

BE IT KNOWN THAT I, Tommy F. Brookey, a citizen of the United States of America, residing in the City of Edmond, County of Oklahoma, State of Oklahoma,

5 have invented new and useful improvements in

APHRON-CONTAINING WELL DRILLING AND SERVICING FLUIDS

of which the following is a specification:

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207

APHRON-CONTAINING WELL DRILLING AND SERVICING FLUIDS

217

Background of the Invention

Formation damage due to invasion by drilling fluids is a well-known problem. Many zones contain formation clays which hydrate when in contact with water such as the filtrate from drilling fluids. These hydrated clays tend to block the producing zones, primarily sands, so that oil and gas cannot move to the borehole and be produced.

These zones are also damaged by solids which are carried into the openings with the fluid. The movement of drilling fluids and filtrate through these openings also causes the dislodging and migration of solids in place in the formation. These solids can lodge and block movement of produced hydrocarbons.

Invasion is caused by the differential pressure of the hydrostatic column which is generally greater than the formation pressure, especially in low pressure or depleted zones. Invasion is also due to the openings in the rock and the ability of fluids to move through the rock, the porosity and permeability of the zone.

Because of this differential pressure, drillers have long used filtrate control mechanisms to control the movement of drilling fluids and filtrate into and through the formation openings. This mechanism involves adding particles to the drilling fluid which are then deposited onto the borehole wall while circulating and drilling. These particles are generally some combination of bentonite, starch, lignins, polymers, barite, and drilled solids. They are used to plug and seal the borehole due to the particle size and shape, and some control is also due to the viscosity of the filtrate when water-soluble polymers are used. Although this wallcake forms a semipermeable

barrier, some filtrate moves through and into the zone both before and after the wallcake is formed.

Wallcake control, then is not complete and some filtrate water is allowed to contact the producing zone. Another disadvantage of wallcake mud is that when filtrate moves through, the solids are screened out and left in the cake. This causes the cake to become thicker and can lead to differential sticking of the drill string.

More recent technology has seen the development of Low Shear Rate Viscosity (LSRV) fluids. LSRV is created by the addition of specialized polymers to water or brines to form a drilling fluid. These polymers have a unique ability to create extremely high viscosity at very low shear rates. These LSRV fluids have been widely used because of their carrying capacity and solids suspension ability. They have been accepted as a way to minimize cuttings bed formation in high angle and horizontal wells, and as a way to reduce barite sag in high weight muds.

Recent studies and field experience indicate that this LSRV is helpful in controlling the invasion of drilling fluids and filtrate by creating a high resistance to movement into the formation openings. Since the fluid moves at a very slow rate, viscosity becomes very high, and the drilling fluid is contained within the borehole with a very slight penetration. This has been beneficial in protecting the zones from damage as well as reducing differential sticking in these fluids. See for example the article entitled "Drill-In Fluids Improve High Angle Well Production", Supplement to the Petroleum Engineer International, March, 1995.

Lost circulation is also a severe problem in rotary drilling. Lost circulation occurs when the differential pressure of the hydrostatic column is much greater than formation pressure. The

openings in the rock are able to accept and store drilling fluid so that none is returned to surface for recirculation. The fluid is lost downhole and can become an expensive and dangerous problem. Lost circulation can lead to hole instability, stuck drill pipe, and loss of well control. At the least, it halts drilling operations and requires expensive replacement volume to be used.

5 In addition to the fluid volume being lost, expensive lost circulation materials (LCM) are required. These are usually fibrous, granular, or flake materials such as can fibers, wood fibers, cottonseed hulls, nut hulls, mica, cellophane, and many other materials. These LCM materials are added to the fluid system so that they may be carried into the loss zone and lodge to form a bridge on which other materials may begin to build and seal. These LCM materials themselves
10 are damaging to the zones, and because they must be carried many times in the drilling fluid to maintain circulation, solids removal is halted and high solids mud results.

Methods of correcting lost circulation of drilling fluids by aerating the drilling fluids are set forth in U.S. Patents 2,818,230 (Davis) and 4,155,410 (Jackson).

The use of underbalanced drilling has increased as the development of low pressure
15 formations has acquired more importance. Horizontal drilling, in particular, has increased the need to drill across zones that are not only low pressure, but highly fractured or permeable. The exposure of numerous fractures or openings having low formation pressures has increased the problem of lost circulation and formation invasion. The necessity of down hole tools many times preclude the use of bridging materials to stop these losses. This has led to the use of
20 underbalanced drilling techniques to control the losses and invasion of these zones. Some of these techniques include the use of air, mist, and foam drilling fluids. Problems with these fluids include hole cleaning, control of formation fluids, corrosion, and requirements for expensive,

often hard to get equipment such as compressors and boosters. Such fluids are not re-circulateable and must be constantly generated as the drilling proceeds.

Summary of the Invention

A new fluid technique combines the use of low shear rate viscosity generating polymers
5 with surfactants to form colloidal gas aphrons at a concentration less than about 15% by volume
in a re-circulateable well drilling and servicing fluid. The aphrons use encapsulated air available
in most circulating fluids. The aphrons reduce the density of the fluid and provide a means of
bridging and sealing of the formations contacted by the fluid as the bubbles expand to fill the
openings exposed while drilling. The low shear rate polymers strengthen the microbubble and
10 also provide a resistance to movement within the formation so that losses of fluid are
substantially reduced as the formation is being drilled. In this way, lost circulation is prevented.
Any fluid which enters the formation is clean and essentially solids-free such that damage of the
formation is significantly less than with solids-containing fluids. Since no solids or particles are
involved in this method, solids removal equipment can be used to keep the fluid as clean as
15 possible.

It is an object of this invention to provide recirculateable well drilling and servicing fluids
which have an enhanced low shear rate viscosity (hereinafter abbreviated to "ELSRV")
containing aphrons.

It is another object of this invention to provide a method of bridging and sealing
20 subterranean formations at the surface of a borehole during well drilling and servicing
operations.

These and other objects of the invention will be obvious to one skilled in the art upon reading this specification and claims.

The process can comprise, consist essentially of, or consist of the stated steps with the stated materials. The compositions can comprise, consist essentially of, or consist of the stated

5 materials.

50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

Description of the Preferred Embodiments of the Invention

The well drilling and servicing fluids of this invention comprise an aqueous liquid having a water-soluble polymer hydrated therein and a surfactant. The polymers useful in the ELSRV fluids of this invention are such that the ELSRV fluids have a "thixotropic index" of at least 10, wherein the thixotropic index is the ratio of the Brookfield viscosity at 0.5 rpm to the Brookfield viscosity at 100 rpm. The thixotropic index is indicative of the shear thinning characteristics of the fluid.

The base aqueous fluid in which the low shear rate modifying polymer is hydrated may be any aqueous liquid which is compatible with the polymer. Thus the base liquid may be fresh water, or a brine containing soluble salts such as sodium chloride, potassium chloride, calcium chloride, sodium bromide, potassium bromide, calcium bromide, zinc bromide, sodium formate, potassium formate, cesium formate, and the like. The brine may contain one or more soluble salts at any desired concentration up to saturation.

The polymers useful in the ELSRV fluids of this invention comprise any water-soluble polymer which increases the low shear rate viscosity of the fluid to produce a fluid exhibiting a high yield stress, shear thinning behavior. Particularly useful are biopolymers produced by the action of bacteria, fungi, or other microorganisms on a suitable substrate. Exemplary biopolymers are the polysaccharides produced by the action of *Xanthomonas compestris* bacteria which are known as xanthan gums. These are available commercially from several sources including: Kelco Oil Field Group, Inc., under the trademarks "Xanvis" and "Kelzan"; Rhone-Poulenc Chimie Fine, under the trademark "Rhodopol 23-p"; Pfizer Inc., under the trademark "Flocon 4800C"; Shell International Chemical Company of London, U.K., under the trademark

“Shellflo ZA”; and Drilling Specialties Company, under the trademark “Flowzan.” See for example U.S. Patent No. 4,299,825 and U.S. Patent No. 4,758,356, each incorporated herein by reference. Other biopolymers useful in the fluids of this invention are the so-called welan gums produced by fermentation with a microorganism of the genus *Alcaligenes*. See for example U.S. Patent No. 4,342,866, incorporated herein by reference. Gellan gums are disclosed in U.S. Patent No. 4,503,084, incorporated herein by reference. Schleroglucan polysaccharides produced by fungi of the genus *sclerotium* are disclosed in U.S. Patent No. 3,301,848, incorporated herein by reference. Commercially available schleroglucan is sold under the trademarks “Polytran” from the Pillsbury Company and “Actigum CS-11” from CECA S.A. Succinoglycan polysaccharides are produced by cultivating a slime-forming species of *Pseudomonas*, *Rhizobium*, *Alcaligenes* or *Agrobacterium*, e.g., *Pseudomonas* sp. NCIB 11264, *Pseudomonas* sp. NCIB 11592 or *Agrobacterium radiobacter* NCIB 11883, or mutants thereof, as described in European Patent No. A40445 or A138255. Commercially available succinoglycan biopolymer is sold by Shell International Chemical Company of London, U.K., under the trademark “Shellflo-S”.

The minimum concentration of the polymer required to increase the low shear rate viscosity of the fluid can be determined by routine testing. Thus the minimum concentration will be an amount sufficient to impart to the fluid the desired low shear rate viscosity. Generally the fluids will contain a concentration from about 0.7 kg/m³ (0.25 ppb) to about 11.4 kg/m³ (4 ppb), preferably from about 1.4 kg/m³ (0.5 ppb) to about 7.1 kg/m³ (2.5 ppb).

The water base borehole fluids of this invention generally may contain materials well known in the art to provide various characteristics or properties to the fluid. Thus the fluids may contain one or more viscosifiers or suspending agents in addition to the polysaccharide required,

weighting agents, corrosion inhibitors, soluble salts, biocides, fungicides, seepage loss control additives, bridging agents, deflocculants, lubricity additives, shale control additives, and other additives as desired.

The borehole fluids may contain one or more materials which function as encapsulating
5 or fluid loss control additives to further restrict the entry of liquid from the fluid to the contacted shale. Representative materials known in the art include partially solubilized starch, gelatinized starch, starch derivatives, cellulose derivatives, humic acid salts (lignite salts), lignosulfonates, gums, synthetic water soluble polymers, and mixtures thereof.

The fluids of this invention should have a pH in the range from about 7.0 to about 11,
10 preferably from 8 to about 10.5. The pH can be obtained as is well known in the art by the addition of bases to the fluid, such as potassium hydroxide, potassium carbonate, potassium humate, sodium hydroxide, sodium carbonate, sodium humate, magnesium oxide, calcium hydroxide, zinc oxide, and mixtures thereof. The preferred base is magnesium oxide.

The surfactants useful in the present invention to create the aphrons must be compatible
15 with the polymers present in the fluid to create the desired low shear rate viscosity. Thus the surfactants will generally be non-ionic or anionic. A test procedure has been devised to determine if a surfactant can be used in the present invention to generate the aphrons. The procedure is as follows:

To a low temperature, low pressure API filtration cell (API Recommended Practice 13 B-
20 1), the cylindrical body of which is made from Plexiglas of thickness 0.5 inch (1.3 centimeters), is added 200 grams of sand having a particle size in the range from 50 mesh to 70 mesh (297 μ m to 210 μ m). This provides a sand bed depth of 2.1 centimeters. No filter paper is used in the

cell. 350 cc of the fluid to be tested is slowly added to the cell, the cell assembled, and 100 psi nitrogen pressure applied. The pressure is released after the nitrogen blows through the bed for 30 seconds. Upon releasing the pressure the sand bed will expand in volume/height as the bubbles in the sand bed expand. The expansion is not even, and an average increase in height of the bed as measured at the cell wall and at the center of the sand bed is obtained. Surfactants which increase the sand bed by at least 50% are considered to be preferred for the generation of aphrons in the present invention. Test Fluid: contains 1.5 pounds per 42 gallon barrel (4.285 kg/m³) of well hydrated xanthan gum in water and 1 pound per 42 gallon barrel (2.857 kg/m³) of surfactant to be tested. The surfactant is dispersed in the xanthan gum dispersion by spatulation to prevent the generation of a foam. Solid surfactants are first dissolved in an appropriate water dispersible or soluble solvent before adding them to the xanthan gum dispersion.

The book by Felix Sebba entitled "Foams and Biliquid Foams - Aphrons", John Wiley & Sons, 1987, incorporated herein by reference, is an excellent source on the preparation and properties of microbubbles.

An aphron is made up of a core which is often spherical of an internal phase, usually liquid or gas, encapsulated in a thin aqueous shell. This shell contains surfactant molecules so positioned that they produce an effective barrier against coalescence with adjacent aphrons.

The aphrons when first generated contain a wide size distribution ranging up to about 200 μ m in diameter. At atmospheric pressure, the aphrons of very small diameter diminish very rapidly leaving aphrons in the 25 μ m to about 200 μ m size range. This is due to the excess pressure within the aphrons which increases as the diameter of the aphrons decreases. Thus the

smaller aphrons will tend to diminish in size by transferring their gas to the larger ones which would have a lower excess pressure.

In the case of the aphron-containing well drilling and servicing fluids of the present invention, the aphrons are generated downhole as the fluid exits the drilling bit. The fluid is under considerable pressure composed of hydrostatic as well as pressure loss created by the circulating system. It is believed that this fluid pressure compensates for the excess pressure within the aphrons such that the aphrons smaller than about 25 μm are stabilized for a period of time until they are circulated up the borehole. The aphrons thus are able to penetrate within the pore spaces of the exposed formation where they can expand, because of the lower pore pressure within the formation, and seal the pore spaces from the entry of any fluid. Microfractures and the like will be filled with aphrons which likewise expand within the formation to seal the microfractures.

Increases in vapor pressure due to pressure drops, temperature increases, and cavitation are common in downhole conditions. Certain solvents which may be present in the fluid may also effect vapor pressure to provide gasses needed to form aphrons.

Aphrons large enough to be seen without magnification can be visually observed in the fluid as it flows from the borehole into the surface holding tanks ("pits") before being recirculated. Generally the fluid flows across a screen to remove the drill cuttings. Screens as fine as 200 mesh (74 μm screen openings) can be used with the fluids of the present invention.

Aphrons greater than the screen size will be removed from the fluid. If desired, the particle size of the aphrons in the fluid can be determined with various particle size analyzers which are commercially available. See for example the following articles: (1) "Microbubbles: Generation

and Interaction with Colloid Particles”, James B. Melville and Egon Matijevic, Chapter 14 in “Foams”, R.J. Akers, editor, Academic Press, 1976; (2) “Separation of Organic Dyes from Wastewater by Using Colloidal Gas Aphrons”, D. Roy, K.T. Valsaraj, and S.A. Kottai, Separation Science and Technology, 27(5), pp. 573-588 (1992). These articles are incorporated
5 herein by reference.

Upon being recirculated down the drill string and through the bit additional aphrons are generated provided the concentration of the surfactant is sufficient. It is desirable to add additional surfactant to the fluid either continuously or intermittently until the desired quantity of aphrons is produced.

10 The quantity of aphrons in the fluid depends on the density required. Generally, the fluid will contain less than 15% by volume of aphrons. Thus the density of the circulating fluid can be monitored on the surface and additional surfactant added as necessary to maintain the desired density, if the density is too high, and weight material may be added if the density is too low. The quantity of aphrons in the fluid can be determined by adding a known quantity of a defoamer
15 or other chemical to destabilize the surfactant-containing shells surrounding the aphrons. Measurement of the change in volume of the fluid will indicate the volume % of aphrons in the fluid.

The concentration of surfactant required in any case is less than the critical micelle concentration (CMC) of the surfactant. Generally a concentration of surfactant from about
20 0.015% by volume to about 0.15% by volume, depending on the particular surfactant present in the fluid, is required, preferably from about 0.03% to about 0.1% by volume assuming the surfactant contains about 80% by weight solids.

If desired, the aphrons can be generated on the surface using the procedures and equipment set forth in the following U.S. Patents, incorporated herein by reference: Sebba Patent No. 3,900,420 and Michelsen Patent No. 5,314,644. The well drilling and servicing fluid containing the aphrons can then be continuously circulated in the borehole.

5 The so-called water-soluble polymer present in the fluid to enhance the low shear rate viscosity of the fluid also helps to stabilize the aphrons, thus helping to prevent their coalescence.

It is preferred that the surfactant be added to the drilling and well servicing fluid under pressure by pumping the surfactant into the fluid.

10 If necessary, air or other gas can be incorporated into the fluid to entrain more gas for forming the aphrons as the fluid exits the drill bit at the bottom of the borehole, provided that the fluid contains less than about 15% by volume of aphrons (encapsulated air or gas).

The following examples are illustrative of this invention and are not to be regarded as limitative.

15 The Lost Circulation Preventative Fluid system (hereinafter sometimes referred to as "LCPF" System) is initially prepared containing 1.5 - 2.0 lbm/bbl (4.285 - 5.714 kg/m³) of xanthan gum biopolymer and 0.075% by volume of a blend of nonionic and anionic surfactants (80% concentration, by weight, in an aqueous solution). This surfactant blend exhibited an average % increase in the height of sand bed test of 55%. The biopolymer is hydrated in the fluid, and the surfactant is injected under pressure into the fluid in the standpipe. The LCPF
20 system has been evaluated as indicated in the Examples.

The low shear rate viscosity was increased for hole cleaning and to create a resistance to movement into the formation, while the polymer encapsulation helped provide strength for the

bubble wall surrounding the aphrons produced downhole as the LCPF system exited the drill bit.

The surfactant solution enabled the aphrons to form, reducing the fluid density and providing “bubble bridging” to seal off the formations drilled.

Example 1

5 BACKGROUND

A horizontal reentry well was planned in the Lodgepole formation in Billings County, North Dakota. The drilling fluid requirements were several. The fluid had to have carrying capacity to carry out milled cuttings as the window was cut. It also would need lubricity and stability in carrying out the drilling operations during the build and lateral section, and the ability
10 to provide invasion control while drilling the Lodgepole producing zone.

Lost circulation prevention was, of course, a necessity since the bottom hole pressure was low and the formation was fractured. Because of the downhole tools, MWD and mud motors, no bridging materials could be used to control losses.

Another factor was the cold weather. Freezing temperatures required some salinity so
15 that cut brine was used, and the resulting base fluid weighted over 9.3 ppg. The fluid then had to provide a measure of lost circulation prevention and invasion control due to this overbalance condition.

For these reasons, the well was planned using the LCPF system.

APPLICATION

20 The LCPF System was prepared and circulated in the borehole and drilling commenced. The milling, kickoff, and build operations were done with no problems. The zone was drilled with the LCPF system containing about 7% by volume aphrons having a density of 8.7 ppg. This low density, along with the invasion control properties of the system allowed the operator to drill the zone successfully.

25 The lateral was drilled as planned with no losses and with excellent hole conditions.

Example 2

BACKGROUND

A well was being drilled in the Sprayberry area of West Texas. Severe lost circulation was common while drilling in this area. It was necessary to carry 12 lbm-bbl (34.3 kg/m³) or more
5 lost circulation material and bypass the solids removal equipment. Whenever lost circulation material content dropped, losses would recur.

Mud problems and poor hole conditions were common due to the buildup of solids and a decision was made to replace the existing system with the LCPF System.

APPLICATION

10 The LCPF System was prepared and circulated in the borehole to displace the fluid in the hole and to create aphrons in the fluid. The aphrons, about 12% by volume, helped to reduce the density from 9.2 to 8.2 ppg and formed a "Bubble Bridge" helping stop fluid movement into the loss zone. Solids removal was resumed and the well was drilled to total depth with no further losses. A subsequent well was being drilled in the area using the LCPF System with no losses
15 and no mud problems.

Example 3

Two re-entry wells were drilled in the North Texas area into the reef portion of the dolomitic zone. This formation was highly vugular with large, interconnected openings. Severe losses had been experienced in this zone.

20 A typical procedure was to drill into the zone, and if it was present, complete returns were lost. To regain circulation meant pumping away large volumes of drilling muds with high concentrations of bridging materials, as high as 35 lbm/bbl (100 kg/m³).

In this area, the problem was compounded by the presence of a gas cap above the reef zone requiring 9.0 ppg fluid to prevent gas entry.

After careful evaluation of the severe problems in this area, a program was designed to provide success in drilling and evaluating these zones by using the LCPF System.

5 APPLICATION

The LCPF System was prepared and drilling commenced while surfactant was injected. When adequate aphrons were generated in the LCPF system, the system was weighted up with barite to 9.0 ppg and the zone was drilled without any lost circulation.

Logging and completion was easily accomplished and the wells were put on production with
10 no cleanup or stimulation required.

Example 4

A horizontal well was planned in the Sisquoc formation in Santa Barbara Co., California. Solutions to several problems were crucial to the success in drilling this well.

The Sisquoc is a multi-layered, water sensitive zone containing clays, shales, and sand.
15 Drilling horizontally across it would require inhibition for shale stability, prevention of cuttings bed buildup in the lateral and build section, and the ability to maintain circulation through the low pressure, unconsolidated sands.

Use of conventional lost circulation material was prohibited since logging while drilling navigation tools would be required to accurately drill the zone. Invasion of the sensitive zone
20 with solids and lost circulation material laden fluid was also discouraged.

For these reasons, the well was planned using the LCPF System.

APPLICATION

The multiple clay, shale and sand zones were drilled with a low density LCPF System. This low density, along with the invasion control properties of the system allowed the operator to drill the zone successfully.

The intermediate was drilled through reactive clay beds and shales while building angle to a casing point of 92° where casing was set with no problems. Previous wells experienced severe problems drilling and running casing through this interval.

The lateral borehole was drilled past 800 feet (243.8 meters) with no losses and good hole conditions. A 6 5/8" slotted liner was run to bottom with no difficulty.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

Example 5

Surfactants were screened for use in the present invention using the test procedure set forth hereinbefore. The average percent increase in height of the sand bed is as follows:

	<u>Surfactant</u>	<u>% Increase</u>
5	Sodium dioctyl sulfosuccinate	118.8
	Chubb National Foam-High Expansion	96.4
	Alpha olefin sulfonate	63.7
	Ethoxylated 2,4,7,9-tetramethyl-5-decyn-4,-diol	56.0
	Linear C ₉ -C ₁₁ alcohol ethoxylates, ave. 6 moles EO/mole	56.0
10	Tetrasodium N-(1,2-dicarboxyethyl)-N-octadecyl sulfosuccinate	50.6
	Mixture of diethanolamides of fatty acids	50.0
	Sodium disopropyl naphthalene sulfonate	38.1
	Linear C ₁₂ -C ₁₅ alcohol ethoxylates, ave. 7 moles EO/mole	38.1
	Modified alkyl ether sulfate	28.6
15	Ethoxylated Octadecylamine-Octadecylguanidine complex	19.0
	Ethoxylated (20 moles) methyl glucoside sesquistearate	19.0
	2,4,7,9-tetramethyl-5-decyne-4,7-diol	<10
	Ethoxylated (1 mole) nonyl phenol	<10
	Sodium alkyl sulfate	<10
20	Polyoxypropylene-polyoxyethylene block copolymer	<10